

The University of Burdwan



Soumen Bhattacharjee

Professor

Department of Botany

UGC Centre of Advanced Studies

Email: sbhattacharjeebot.buruniv.ac.in

Mobile: +919433778493

Golapbag Campus
Burdwan - 713104
West Bengal, India

Date: 19.05.2017

Tender Notice

Tender Title:

Sealed quotations are invited from the interested vendors for the following items needed for a DST(WB) Grant (PI: Professor Soumen Bhattacharjee), Department of Botany BU.

Date: 19.05.2017

Tender No: DST(WB)/SB/Bot BU/17

Tender Date: 19.05.2017

Last date for tender submission: 02.06.2017

Items:

Name of items with specifications

General Terms & Conditions:

1. All prices should be quoted in INR only.
2. Prices are to be quoted inclusive of VAT and delivery charges, if any. Incomplete items will be rejected.
3. Sealed Envelope containing quotation should be super scribed as "Quotation for Tender No for a DST (WB) Grant (PI: Professor Soumen Bhattacharjee) Department of Botany BU".
4. Tender No. should be mentioned on the envelope positively.
5. Warranty One year additional / extended warranty for 2nd year, beyond the 1st year's warranty.
6. Payments terms: Payment will be made after successful installation & commissioning of the AC's.
7. Delivery schedule: After receipt of the work order the materials should be delivered within one month & if any defect of the supplied items is found, it should be replaced immediately form vendor's side.

Submission of Quotations:

Quotations may be submitted to: Professor Soumen Bhattacharjee, Dept. of Botany, Golapbag, The University of Burdwan, Burdwan, Pin: 713104, WB on or before 26th May, 2017 between 11.00 A.M. and 5.00 P.M.

1. Cold Centrifuge (Remi, C-24 Plus) with voltage stabilizer (VC03)**Specifications:**

Speed: 18000 RPM, RCF 31150;

Capacity 12x15 ml,

R244 M;

Lowest temperature -8⁰ C, WxDxH : 775x575x475

Internal dimension 660x655x450, External dimension 800x1095x1020

(Quote the price of Voltage stabilizer separately)

2. Seed Germinator (Remi SG 6) with Voltage stabilizer (VS04)**Specifications:**

Microprocessor controlled with LCD display

Temperature range 10⁰ to 60⁰ C, Humidity range 40% to 95% with capacity type sensor for precise control of temperature and humidity

Battery backup for controller 12V

Automatic calibration of set parameters

Adjustable trays

Low water run alarm

Door open, humidity variation and power failure alarm

Illumination: 8 Watt florescent lamp

(Quote the price of Voltage stabilizer separately)